



PAR25 Halogen PAR Lamps





Conventional Spot Stippled lens



Conventional Flood Beaded spread lens




- Colour temperature 2900K for aluminium version and 3000K for dichroic version
- Average Life 3000 hours



Lamp Code	Voltage (V)	Wattage (W)	Beam Spread	Intensity (cd)	Base	Diameter D (mm)	Length L (mm)
PAR25/50W	230/240	50	Spot	4000	E27	80	103
PAR25/50W	230/240	50	Flood	1100	E27	80	103
PAR25/75W	230/240	75	Spot	5500	E27	80	103
PAR25/75W	230/240	75	Flood	1300	E27	80	103


PAR30 Halogen PAR Lamps, Conventional Style





Conventional Spot Stippled lens



Conventional Flood Beaded spread lens



- Colour temperature 2900K for aluminium version and 3000K for dichroic version
- Average Life 3000 hours



Lamp Code	Voltage (V)	Wattage (W)	Intensity (cd)		Base	Diameter D (mm)	Length L (mm)
			Spot	Flood			
PAR30/50W	120/130	50	4000	1300	E26	95	90
PAR30/75W	120/130	75	6500	2000	E26	95	90
PAR30/75W	230/240	75	6500	2000	E27	95	92
PAR30/100W	230/240	100	9000	3000	E27	95	92