


# Compact Fluorescent Lamps

with Integral Starter For Conventional Control Gear (CCG)




Lamp Code	Voltage (V)	Wattage (W)	CRI (Ra)	Lumen	Base	Length L (mm)
FLS-5W	110-130 / 220-240	5	80-89, 1B	250	G23	108
FLS-7W	110-130 / 220-240	7	80-89, 1B	400	G23	137
FLS-9W	110-130 / 220-240	9	80-89, 1B	600	G23	167
FLS-11W	220 – 240	11	80-89, 1B	900	G23	237
<b>North American System</b>						
F13TT	110 – 130	13	80-89, 1B	900	GX23	185

## FLS and FLD

- Extremely slim with small dimensions
- 10 times the life and only 20% of power consumption of ordinary light bulbs
- Excellent colour rendition 80-89, 1B
- Colour available :
 

827 =	2700K
830 =	3000K
835 =	3500K
840 =	4200K
865 =	6500K



Lamp Code	Voltage (V)	Wattage (W)	CRI (Ra)	Lumen	Base	Length L (mm)
FLD-10W	220 – 240	10	80-89, 1B	600	G24d1	110
FLD-13W	220 – 240	13	80-89, 1B	900	G24d1	138
FLD-18W	220 – 240	18	80-89, 1B	1200	G24d2	153
FLD-26W	220 – 240	26	80-89, 1B	1800	G24d3	172
<b>North American System</b>						
F9DTT	110 – 130	9	80-89, 1B	600	G23-2	109
F13DTT	110 – 130	13	80-89, 1B	900	GX23-2	120