


Compact Fluorescent Lamps For External Starters, Conventional and Electronic Control Gear (ECG) and Dimmer Systems



Lamp Code	Wattage (W)	CRI (Ra)	Lumen (lm)	Base	Length L (mm)
FLT/E-13W	13	80-89, 1B	900	GX24q1	106
FLT/E-18W	18	80-89, 1B	1200	GX24q2	116
FLT/E-26W	26	80-89, 1B	1800	GX24q3	131
FLT/E-32W	32	80-89, 1B	2400	GX24q3	147
FLT/E-42W	42	80-89, 1B	3200	GX24q4	168

FLT/E and FLL :

- ➔ Extremely slim with small dimensions
- ➔ Eight times the life and only 20% of power consumption of ordinary light bulbs
- ➔ Excellent color rendition
- ➔ Colour available :

827	=	2700K
830	=	3000K
835	=	3500K
840	=	4200K
865	=	6500K



Lamp Code	Wattage (W)	CRI (Ra)	Lumen (lm)	Base	Length(wo/pins) L (mm)
FLL-18W	18	80-89, 1B	1200	2G11	217
FLL-24W	24	80-89, 1B	1800	2G11	317
FLL-36W	36	80-89, 1B	2900	2G11	411
FLL-L-34W	34	80-89, 1B	2700	2G11	533
FLL-L-36W	36	80-89, 1B	2900	2G11	533
FLL-40W*	40	80-89, 1B	3150	2G11	533
FLL-55W*	55	80-89, 1B	4800	2G11	533
North American Rapid Start ECG only					MOL(w/pins)
FLL-18W/RS	18	80-89, 1B	1200	2G11	10.5 in.
FLL-40W/RS	40	80-89, 1B	3150	2G11	20.5 in.

*for ECG operation only