




Single Ended Metal Halide Lamps

For Enclosed Fixtures, European System



- High Luminous efficacy with very good color rendition
- Universal burning position
- Long burning hours



* 250/400W lumen data – please refer to next two pages on technical details of MH 250W and 400W

Lamp Code	Description	Wattage (W)	Lumen (lm)	Base	Diameter D (mm)	Length L (mm)
Elliptical bulb						
MH-E70/WDL/CL	MH70W/ED54/clear/E27/3K	70	5200	E27	55	137±3
MH-E70/WDL	MH70W/ED54/coated/E27/3K	70	4800	E27	55	137±3
MH-E70/NDL/CL	MH70W/ED54/clear/E27/4K	70	5500	E27	55	137±3
MH-E70/NDL	MH70W/ED54/coated/E27/4K	70	5100	E27	55	137±3
MH-E100/WDL/CL	MH100W/ED54/clear/E27/3K	100	8400	E27	55	137±3
MH-E100/WDL	MH100W/ED54/coated/E27/3K	100	7800	E27	55	137±3
MH-E100/NDL/CL	MH100W/ED54/clear/E27/4K	100	8400	E27	55	137±3
MH-E100/NDL	MH100W/ED54/coated/E27/4K	100	7800	E27	55	137±3
MH-E150/WDL/CL	MH150W/ED54/clear/E27/3K	150	12500	E27	55	137±3
MH-E150/WDL	MH150W/ED54/coated/E27/3K	150	11800	E27	55	137±3
MH-E150/NDL/CL	MH150W/ED54/clear/E27/4K	150	12500	E27	55	137±3
MH-E150/NDL	MH150W/ED54/coated/E27/4K	150	11800	E27	55	137±3
MH-E250/NDL	MH250W/ED90/coated/E40/4K	250	*18000-25000	E40	90	203±3
MH-E250/D(3.0A)	MH250W/ED90/coated/E40/6K	250	19000	E40	90	203±3
MH-E400/NDL	MH400W/ED118/coated/E40/4K	400	*35000-40000	E40	120	275±3
MH-E400/D(4.0/4.4A)	MH400W/ED118/coated/E40/6K	400	30000	E40	120	275±3
Tubular bulb						
MH-T250/NDL	MH250W/T46/clear/E40/4K	250	*17000-22000	E40	46	259±3
MH-T250/D(3.0A)	MH250W/T46/clear/E40/6K	250	19000	E40	46	259±3
MH-T400/NDL	MH400W/T46/clear/E40/4K	400	*34000-38000	E40	46	281±3
MH-T400/D(4.0/4.4A)	MH400W/T46/clear/E40/6K	400	30000	E40	46	281±3
MH-T600/D(6.2A)	MH600W/T46/clear/E40/6K	600	50000	E40	80	340±3
MH-T1000/NDL(8.0A)	MH1000W/T64/clear/E40/4K	1000	80000	E40	64	377±3