

LED Downlight ND291 E-299E

9W


Features

- 9W LED Downlight
- Recessed round, uniform distribution
- Twist-lock changeable LED module for inventory cost saving
- Ideal replacement up to 100W halogen downlight
- Adjustable tilting angle of ± 23° vertically (ND293E, ND294E, ND296E, ND297E, ND298E)
- Beam angle: 20° / 30° / 38° / 50°
- Cut out dimensions Ø75mm / 75x75mm
- Good color rendition, Ra ≥80 / 90



Diagrams

Dimensions:



ND292E - ND299E:



Twist-lock changeable LED module:



Standards



IP20

IP54

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

©2024 Prosperity Lamps & Components Ltd. All rights reserved

Applications


Home


Office


Shopping mall


Hotel


Supermarket


Restaurant


Gallery


Museum

Technical Data	
Type of Light Source	
Lighting Technology Used	LED
Non-directional or Directional [NDLS/DLS]	DLS
Mains or Non-mains [MLS/NMLS]	MLS
Connected Light Source	No
Color tunable light source	No
Envelop [No/Second/Non-Clear]	No
High Luminance Light Source	No
Anti-glare Shield	No
Electrical	
Rated Wattage [W]	9W
On-mode Power [W]	9W
Standby Power [W]	N/A
Networked Standby Power [W]	N/A
Rated Voltage [V/Hz]	220-240V, 50/60Hz
Power Factor	0.9
Input Current [mA] @230V	43
Model	
ND291E-9W/8XX	9W
ND292E-9W/8XX	9W
ND293E-9W/8XX	9W
ND294E-9W/8XX	9W
ND295E-9W/8XX	9W
ND296E-9W/8XX	9W
ND297E-9W/8XX	9W
ND298E-9W/8XX	9W
ND299E-9W/8XX	9W
Luminous Flux (Useful Luminous Flux) [lm]	
9W	760lm (740lm) @3000K
	830lm (805lm) @4000K
	920lm (890lm) @6500K

Peak Luminous Intensity [cd]	
9W 20°	2700 @3000K
	3200 @4000K
	4100 @6500K
9W 30°	2500 @3000K
	3000 @4000K
	3900 @6500K
9W 38°	2300 @3000K
	2800 @4000K
	3700 @6500K
9W 50°	2100 @3000K
	2600 @4000K
	3500 @6500K
Performance	
SCDM	<6
Chromaticity coordinates [x, y]	0.44, 0.403@3000K / 0.38, 0.38@4000K / 0.312, 0.335@6500K
Efficacy [lm/W]	82-99
Color Rendering Index [Ra]	80 / 90
R9 colour rendering index value	2
Beam Angle [°]	20 / 30 / 38 / 50
Rated Life, Ta@25°C [hrs]	50,000
Lamp Survival Factor	0.9
Lumen Maintenance	0.96
Number of Switching Cycles Before Failure	25,000
Starting Time [S]	<0.5
Warm Up Time [S]	<2
Premature Failure At 1000hrs	<5%
Displacement Factor [cosØ]	0.5
Flicker Metric [Pst LM]	1
Stroboscopic Effect Metric [SVM]	0.4
Mechanical	
Diameter D [mm]	88(ND291E-ND294E, ND297E-ND298E)
Height H1 [mm]	85(ND291E-ND296E, ND299E) / 101(ND297E) / 105(ND298E)
Height H2 [mm]	48(ND291E-ND296E, ND299E) / 64(ND297E) / 68(ND298E)
Length L [mm]	88(ND295E-ND296E, ND299E)
Width W [mm]	88(ND295E-ND296E, ND299E)
Cut out dimensions [mm]	Ø75(ND291E-ND298E) / 75 x 75(ND299E)
Material	Body: Die-cast aluminium
	Trim: Die-cast aluminium
	Reflector: High purity, anodized aluminium
Standard Compliance	
CE-LVD	EN60598-1, EN60598-2-2
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Environment	RoHS
Mercury Content [mg]	0.0
Energy Class	3000K / 4000K / 6500K
9W	F / F / E
Electrical Class	II
Other	
Dimmable [Yes/Only with specific dimmers/No]	No
Operation Temperature	-10°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Energy Consumption in on-mode [kWh/1000h]	9kWh