

Ceramic LED G9

3.5W


Features

- Extremely energy saving with low power consumption
- Ideal retrofit of traditional G9 with same appearance / performance / dimensions
- Overall light distribution
- Lamp weight 12g comply with IEC G9 requirement
- Universal burning position
- Good color rendition, Ra ≥80



Diagrams

Dimensions:



Standards



Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Applications



Home



Shopping mall



Hotel



Supermarket



Restaurant

Technical Data

Type of Light Source

Lighting Technology Used	LED
Non-directional or Directional [NDLS/DLS]	NDLS
Mains or Non-mains [MLS/NMLS]	MLS
Connected Light Source	No
Color tunable light source	No
Envelop [No/Second/Non-Clear]	No
High Luminance Light Source	No
Anti-glare Shield	No

Electrical

Rated Wattage [W]	3.5W
On-mode Power [W]	3.5W
Standby Power [W]	N/A
Networked Standby Power [W]	N/A
Rated Voltage [V/Hz]	220-240Vac, 50/60Hz
Power Factor @230V	0.4
Input Current [mA] @230V	38

Model

LED C G9 3.5W	3.5W
---------------	------

Luminous Flux (Useful Luminous Flux) [lm]

3.5W	320lm @3000K
	330lm @4000K
	340lm @6500K

Performance

SCDM	<6
Chromaticity coordinates [x, y]	0.44,0.403@3000K / 0.37,0.38@4000K / 0.312,0.335@6500K
Efficacy [lm/W]	91-97
Color Rendering Index [Ra]	≥80
R9 colour rendering index value	2
Beam Angle [°]	360
Rated Life, Ta@25°C [hrs]	25,000
Lamp Survival Factor	0.9
Lumen Maintenance	0.96
Number of Switching Cycles Before Failure	>15,000

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Starting Time [S]	<0.5
Warm Up Time [S]	<2
Premature Failure At 1000hrs	<5%
Displacement Factor [cosØ]	0.5
Flicker Metric [Pst LM]	1
Stroboscopic Effect Metric [SVM]	0.4
Mechanical	
Diameter D [mm]	Φ16
Height H [mm]	53
Base	G9
Material	Ceramic
Standard Compliance	
CE-LVD	EN62560
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
CE-EMF	EN62493
Environment	RoHS
Mercury Content [mg]	0.0
Energy Class	F
Other	
Dimmable [Yes/Only with specific dimmers/No]	No
Operation Temperature	-20°C ~ 50°C
Storage Temperature	-10°C ~ 30°C
Claim of Equivalent Power, 3.5W [W]	31W
Energy Consumption in on-mode [kWh/1000h]	4kWh

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com