

Filament-LED ST26

1.4W/2.6W


Features

- Extremely energy saving with low power consumption
- Full glass version ideal retrofit of incandescent Pygmy and traditional lamps with same appearance / performance / dimensions
- Suitable for Refrigerator light, Cooker hood light and Night light
- Operation temperature -20°C to 60°C
- Overall light distribution
- Good color rendition, Ra \geq 80



Diagrams

Dimensions:



Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Standards



Applications



Home



Shopping mall



Hotel



Supermarket



Restaurant

Technical Data	
Type of Light Source	
Lighting Technology Used	LED
Non-directional or Directional [NDLS/DLS]	NDLS
Mains or Non-mains [MLS/NMLS]	MLS
Connected Light Source	No
Color tunable light source	No
Envelop [No/Second/Non-Clear]	No
High Luminance Light Source	No
Anti-glare Shield	No
Electrical	
Rated Wattage [W]	1.4W / 2.6W
On-mode Power [W]	1.4W / 2.6W
Standby Power [W]	N/A
Networked Standby Power [W]	N/A
Rated Voltage [V/Hz]	220-240Vac, 50/60Hz
Power Factor @230V	0.3 / 0.46
Input Current [mA] @230V	20 / 25
LED	2pcs strips
Model	
LED ST26 FIL-1.4W-G CL	1.4W
LED ST26 FIL-2.6W-G CL	2.6W
Luminous Flux (Useful Luminous Flux) [lm]	
1.4W	140lm @2700K
2.6W	280lm @2700K
Performance	
SCDM	<6
Chromaticity coordinates [x, y]	0.463,0.42@2700K

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com

Efficacy [lm/W]	100-108
Color Rendering Index [Ra]	≥80
R9 colour rendering index value	2
Beam Angle [°]	360
Rated Life, Ta@25°C [hrs]	25,000
Lamp Survival Factor	0.9
Lumen Maintenance	0.96
Number of Switching Cycles Before Failure	>15,000
Starting Time [S]	<0.5
Warm Up Time [S]	<2
Premature Failure At 1000hrs	<5%
Displacement Factor [cosØ]	0.5
Flicker Metric [Pst LM]	1
Stroboscopic Effect Metric [SVM]	0.4
Mechanical	
Diameter D [mm]	Φ26
Height H [mm]	61
Base	E14 / B15d
Material	Glass
Standard Compliance	
CE-LVD	EN62560
CE-EMC	EN55015, EN61547, EN61000-3-2, EN61000-3-3
CE-EMF	EN62493
Environment	RoHS
Mercury Content [mg]	0.0
Energy Class	F
Other	
Dimmable [Yes/Only with specific dimmers/No]	No
Operation Temperature	-20°C ~ 50°C
Storage Temperature	-10°C ~ 30°C
Claim of Equivalent Power, 1.4W [W]	15W
Claim of Equivalent Power, 2.6W [W]	25W
Energy Consumption in on-mode [kWh/1000h]	2kWh / 3kWh

Prosperity Lamps & Components Ltd.

Tel: (852) 2511 0022 Fax: (852) 2511 0082 Web: www.prosperitylamps.com Email: info@prosperitylamps.com